

L SERIES

INDUSTRIAL PISTON AIR COMPRESSORS

Oil-Free & Lubricated 0.7 - 20 hp



Oil-free Piston Compressors

LF, LFx, LFD & LZ Series

LF: Single-stage, two-cylinder, oil-free, reciprocating compressor with a maximum working pressure of 145 psi.



LFx: Single-stage, one-cylinder, oil-free, reciprocating compressor with a maximum working pressure of 145 psi.



LFxD: Single-stage, oil-free, reciprocating compressor with integrated dryers and a maximum working pressure of 145 psi.



LZ: Automatically or Elektronikon® Mk5-controlled, single-stage, oil-free, reciprocating compressor, silenced, with a maximum working pressure of 145 psi.



Lubricated Piston Compressors

LE & LT Series / LB Series (High Pressure)

LE: Single-stage, reciprocating compressor with a maximum pressure of 145 psi.



LT: Two-stage, reciprocating compressor with a maximum pressure of 218, 290, or 435 psi.

LB Boosters: Single-stage, lubricated, air and nitrogen booster with a maximum pressure of 580 psi.



Two-stage, lubricated, nitrogen booster with a maximum pressure of 4353 psi.

Adams-ISC, LLC.

2090 Deadwood Ave.
Rapid City, SD 57702
605-342-3275



Authorized distributor

